

Shower toilet, rimless, wall-hung with seat and cover 82060.1 ... 000 1



TECHNICAL DATA

| | | | |
|------------------------------|---|--|--|
| Order no. | 82060.1 ... 000 1 | Power supply & consumption | concealed Rated voltage 220 to 230 V, 50/60 Hz Direct connection by NYM cable possible External connection with Laufen cable routing possible, order no. 89560.3 (to be ordered separately) |
| Certified to | CE, IPX4, EN 13077, SVGW Drinking water standards EN 1717 | Weight | 33,0 kg |
| matching for | LIS CW2 Concealed frame with cistern for shower toilets, order no. 89466.1, 89466.6 | Accessories incl. | Rotary button for shower function |
| Specifications | Shower toilet, rimless, wall-hung, with ceramic surface refinement LCC (only white) Washdown, flushing from 6 l to 4.5 l Concealed fixation Rotary button for shower function | Mounting acc. incl. | Inlet and outlet pipes, fastening kit M12 with connection plate, incl. mounting tool, sound insulation set (DIN 4109) and water connection set for shower toilet |
| Functions | Rear shower adjustable in pressure & position Oscillation function Temperature adjustable via mobile app (ios/Android) Self cleaning of shower head before and after every use Exchangeable shower head is fully recessed in the ceramic with a cover ring LED signal light Integrated descaling function | Mounting acc. excl. | Adapter plate for Cleanet Navia Shower Toilet, order no. 89469.0 External cable routing, order no. 89560.3 Stone screw fastening kit M12 |
| Water pressure & temperature | Shower 7 pressure levels Flow rate ca. 3.5 l/min Temperature level via mobile app (ios/Android) | Colours | 400 – White LCC, 757 – White matt |
| Water inlet | concealed, G 3/8" | SPECIFICATION TEXT | |
| Outlet | DN 90 mm horizontal | Shower toilet, rimless, wall-hung, washdown Laufen CLEANET NAVIA toilet pan sanitary ceramic, with ceramic surface refinement LCC (only white) | |
| WC seat and cover | included Duroplast, removable, with lowering system, order no. 89160.1 | WC seat and cover Duroplast, removable, with lowering system CE, IPX4, EN 13077, SVGW, Drinking water standards EN 1717 min. 4.5/3-l-flush, dimensions 370 x 580 x 380 mm, concealed fixation Special feature: Rear shower, with adjustable water pressure and position, temperature adjustable via mobile app (ios/Android), oscillation function, integrated self cleaning shower head before and after every use, LED signal light, concealed water supply and power supply Order no. 82060.1 ... 000 1 | |

TECHNICAL DRAWINGS / S 1 : 20

